



2-Port Hybrid™ DVI KVM Switch with Audio

Diagram



Features

- One console (DVI monitor, PS/2 keyboard, and USB mouse) controls two computers
- Fully DVI-Digital specification compliant
- Remote port selection switch for convenient switch placement
- Supports multi-function mice
- USB 2.0 mouse port can be used for USB hub and USB peripheral haring
- Compact design, built in all-in-one cables (console 1.2m; computers 0.6m, 1.2m)
- Audio (microphone and speaker) enabled -full bass response provides a rich experience for 2.1 surround sound systems
- Independent switching of the KVM and Audio focus - one computer can have the KVM focus while the other has the audio focus
- Superior video quality- up to 1920 x 1200@60Hz; DDC2B
- Auto Scan function to monitor computer operation
- HDCP compliant
- Non-powered

Specifications

Function			CS52D
Computer Connections			2
Port Selection			Hotkey, Pushbutton
Connectors	Console Ports	Keyboard	1 x 6-pin Mini-DIN Female (Purple)
		Video	1 x DVI Male (Black)
		Mouse	1 x USB Type A Female (Black)
		Speaker	1 x Mini Stereo Jack Female (Green)
		Microphone	1 x Mini Stereo Jack Female (Pink)
		Remote Switch	1 x Mini Stereo Jack
	KVM Ports	Keyboard	2 x 6-pin Mini-DIN Male (Purple)
		Video	2 x DVI Male (Black)
		Mouse	2 x USB Type A Male (Black)
		Speaker	2 x Mini Stereo Plug Male (Green)
		Microphone	2 x Mini Stereo Plug Male (Pink)
		Remote Switch	1 x Mini Stereo Jack
Switches	Port		1 x Pushbutton
LEDs	Selected		2 (Green)
Cable Length	Console	KB/Mouse	0.15m
		Video	1.2m
	Computers		0.6m, 1.2m
Emulation	Keyboard		PS/2
Video			1920 x 1200 @60Hz; DDC2B
Scan Interval			3, 5, 10, 20 Seconds
Environment	Operation Temp.		0-50° C
	Storage Temp.		-20-60° C
	Humidity		0 - 80% RH, Non-condensing
Physical Properties	Housing		Plastic
	Weight		0.61 kg
	Dimension (L x W x H)		8.45 x 3.40 x 2.13 cm

* The specifications and pictures are subject to change without notice.