

Philips
Scart cable

5 m

Composite A/V + S-Video

SWV6335



Enjoy the ultimate viewing experience

with this premium A/V cable

Take your components to optimum performance. This top-of-the-range cable offers the best connection for transferring audio/video signals between components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimise signal
- 4-Cut connectors for secure connections
- Split centre pin for better signal transfer
- 99.97% Oxygen-Free Copper (OFC)

Protects against signal loss

- 100% aluminium shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper-braided shielding
- Foam Polyethylene (FPE) Dielectric

Easy installation

- Colour-coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

PHILIPS
sense and simplicity

Scart cable
5 m Composite A/V + S-Video

Specifications

Packaging Data

- Quantity: 1
- EAN/UPC/GTIN: 87 10895 93475 6
- Gross weight: 1.18 kg
- Tare weight: 0.21 kg
- Net weight: 0.97 kg
- Length: 330 mm
- Width: 255 mm
- Height: 120 mm

Inner Box

- EAN/UPC/GTIN: 87 10895 97046 4
- Quantity: 2
- Gross weight: 3.16 kg
- Tare weight: 1.22 kg

- Net weight: 1.94 kg
- Length: 345 mm
- Width: 255 mm
- Height: 270 mm

Outer Box

- EAN/UPC/GTIN: 87 10895 97047 1
- Quantity: 4
- Gross weight: 7.78 kg
- Tare weight: 3.9 kg
- Net weight: 3.88 kg
- Length: 530 mm
- Width: 365 mm
- Height: 290 mm

SWV6335/I0

Product highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

4-Cut connectors

4-Cut connectors ensure secure connections between your component and your cable.

Split centre pin

The split centre pin allows for better signal transfer and an improved connection to the component inputs.

99.97% OFC solid conductor

99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

100% aluminium shielding

This protective layer of aluminium guards against electromagnetic interference for improved signal quality.

Twisted high-purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Copper-braided shielding

This protective layer of copper blocks radio frequency interference for improved signal quality.

FPE Dielectric

Foam Polyethylene (FPE) dielectric is a superior insulation material that protects against signal loss.

Colour-coded connectors

Colour-coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.



Issue date 2008-10-11

Version: 2.0.4

12 NC: 9082 100 06399
EAN: 87 10895 93475 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com