

KVR533D2S4/512
512MB 64M x 64-Bit DDR2-533
CL4 200-Pin SODIMM

DESCRIPTION:

This document describes ValueRAM's 64M x 64-bit (512MB) CL4 DDR2-533 SDRAM (Synchronous **DRAM**) memory module. The components on this module include eight 64M x 8-bit (16M x 8-bit x 4 Bank) DDR2-533 SDRAM in FBGA packages. This 200-pin SODIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

FEATURES:

✓	Clock Cycle Time (tCK) CL=4	3.75ns (min.) / 8ns (max.)
✓	Row Cycle Time (tRC)	55ns (min.)
✓	Refresh to Active/Refresh Command Time (tRFC)	75ns
✓	Row Active Time (tRAS)	40ns (min.) / 70,000ns (max.)
✓	Single Power Supply of	+1.8V (+/- .1V)
✓	Power	1.476 W (operating)
✓	UL Rating	94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 30mm.




Figure 1: KVR533D2S4/512 200-Pin SODIMM