

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100**Current version :** 1.1.1, issued: 27.10.2022**Replaced version:** 1.1.0, issued: 10.09.2015**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****Boardmarker refill ink 119502 (red) contained in: TZ 100****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Refill ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

Legamaster International B.V.

Kwinkweerd 62

Postbus 111

7240 AC Lochem

The Netherlands

Telephone no. +31 (0) 573-713000

Information provided by / telephone

+31 (0) 573-713000

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07

Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100

Current version : 1.1.1, issued: 27.10.2022

Replaced version: 1.1.0, issued: 10.09.2015

Region: GB

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	ethanol	pls. refer to footnote (1)	
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50.00 - < 70.00 wt%
2	1-methoxy-2-propanol		
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10.00 - < 25.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

SECTION 4: First aid measures
4.1 Description of first aid measures
General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100**Current version :** 1.1.1, issued: 27.10.2022**Replaced version:** 1.1.0, issued: 10.09.2015**Region:** GB**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixtureIn the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)**5.3 Advice for firefighters**

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100

Current version : 1.1.1, issued: 27.10.2022

Replaced version: 1.1.0, issued: 10.09.2015

Region: GB

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
List of approved workplace exposure limits (WELs) / EH40			
	Ethanol		
	WEL long-term (8-hr TWA reference period)	1920 mg/m ³	1000 ppm
2	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m ³	100 ppm
	Skin resorption / sensibilisation	Skin	
List of approved workplace exposure limits (WELs) / EH40			
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m ³	100 ppm
	Comments	Sk	

8.2 Exposure controls
Appropriate engineering controls

No data available.

Personal protective equipment
Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

State of aggregation
liquid
Form
liquid

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100

Current version : 1.1.1, issued: 27.10.2022

Replaced version: 1.1.0, issued: 10.09.2015

Region: GB

Colour		
red		
Odour		
characteristic		
pH value		
No data available		
Boiling point / boiling range		
Value	78	°C
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Value	13	°C
Ignition temperature		
Value	287	°C
Auto-ignition temperature		
Comments	Product is not selfigniting.	
Explosive properties		
The product is not explosive. Formation of explosive/highly flammable air-vapour mixtures is possible during/after use.		
Flammability		
No data available		
Lower explosion limit		
Value	1.7	% vol
Upper explosion limit		
Value	15.0	% vol
Vapour pressure		
Value	59	hPa
Reference temperature	20	°C
Relative vapour density		
No data available		
Relative density		
No data available		
Density		
no data available		
Solubility in water		
Comments	partially miscible	
Solubility		
No data available		
Partition coefficient n-octanol/water (log value)		
No data available		
Kinematic viscosity		
No data available		
Solvent content		
Value	79.1	%
Particle characteristics		
No data available		

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100

Current version : 1.1.1, issued: 27.10.2022

Replaced version: 1.1.0, issued: 10.09.2015

Region: GB

9.2 Other information

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		5660	mg/kg bodyweight
Species	rat		
Source	Manufacturer		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		9999.99	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		
Acute inhalational toxicity			
No data available			
Skin corrosion/irritation			
No data available			
Serious eye damage/irritation			
No data available			
Respiratory or skin sensitisation			
No data available			
Germ cell mutagenicity			
No data available			
Reproduction toxicity			
No data available			
Carcinogenicity			
No data available			
STOT - single exposure			
No data available			

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100**Current version :** 1.1.1, issued: 27.10.2022**Replaced version:** 1.1.0, issued: 10.09.2015**Region:** GB**STOT - repeated exposure**

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity****Toxicity to fish (acute)**

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information**Other information**

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100

Current version : 1.1.1, issued: 27.10.2022

Replaced version: 1.1.0, issued: 10.09.2015

Region: GB

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information
14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulations
Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Trade name: Boardmarker refill ink 119502 (red) contained in: TZ 100**Current version :** 1.1.1, issued: 27.10.2022**Replaced version:** 1.1.0, issued: 10.09.2015**Region:** GB**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: P5b

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 643863