

# 605627 Cat.6A Platinum S/FTP Patch Cable, 0.5m , Red

## Product Images



## Compatible



TV



IP Camera



Desktop



Laptop



RJ45



Switch



Server



Router



RJ45





**Underwriters  
Laboratories**



**Compliance Statement**

Screened Category 6A  
ISO/IEC, EN & ANSI/TIA  
Communication Cable

## Short Description

---

1. 4 x 2 AWG 26/7
2. 500MHz performance Bandwidth
3. Transmission: 10Gbit
4. Suitable for PoE, PoE+, PoE++
5. Stranded bare copper conductor
6. Foil and braid shield Reduces EMI/RFI interference
7. PIMF (Pairs in metal Foil)
8. Molded boot with Strain relief
9. RoHS compliant
10. Low Smoke Zero Halogen (LSZH/LSOH)
11. with 3P certificate and UL listed
12. Compliant with ISO/IEC 11801 and EN 50173

## Description

---

Cat.6A Pro S/FTP Patch Cord is composed of preeminent materials and fully-examined to Cat.6A Platinum S/FTP Patch Cord is composed of preeminent materials and fully-examined to conform with industrial standards. Offering higher bandwidth and better signal-to-noise margin, the Cat.6A cable is able to deliver ultrahigh and error-free performance in the most demanding network environments, specially for 10G application.

## Additional Information

---

Approval and compliance RoHS, 3P

Conductor material Copper

Conductor size (AWG) 26AWG

Jacket material LSZH

Category Cat.6A

Flat cable No

|                        |                       |
|------------------------|-----------------------|
| Shielded               | Yes                   |
| Product weight (kg)    | 0,035                 |
| Cable length           | 0,5m                  |
| Color                  | Red                   |
| EAN                    | 4015867152386         |
| Model number           | 605627                |
| Package contents       | 605627                |
| Cable Length           | 0.50m                 |
| Shielding              | S/FTP                 |
| Connector 1            | RJ45 male             |
| Connector 2            | RJ45 male             |
| Dimensions (W x D x H) | 8.34 x 11.68 x 500 mm |

