



HP Permanent Gloss Adhesive Vinyl is an affordable, highly opaque adhesive media with a glossy finish, providing bright and vivid colours. It features a permanent adhesive while offering clean removability.

Ideal for mid-volume print service providers (PSPs) looking for well-priced, high-quality self-adhesive vinyl.

HP Permanent Gloss Adhesive Vinyl is suitable for a wide range of indoor and outdoor applications like advertisements, POP/POS and event signage. Features a permanent adhesive and is easy to handle and mount, whilst offering clean removability.

Highly opaque media offers a durable, high-quality look and fits a wide variety of application needs. Get optimal results on HP Latex printers. It offers weather-resistance with no additional lamination.

This 3.5 mil self-adhesive vinyl maintains a high-quality look across a wide range of indoor and outdoor applications. Permanent adhesive provides strong adhesion and is easily removable.

HP Permanent Gloss Adhesive Vinyl

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

Weight	270 g/m ² (with liner), 145 g/m ² (without liner) per ISO 536 Test Method		
Thickness	3.5 mil/90 microns (without liner or glue), 9.4 mil/230 microns (with liner) per ISO 534 Test Method		
Opacity	Greater than 95% (w/o liner) per TAPPI T-425 Test Method		
Lamination	Yes (Cold)		
Finish	High-gloss		
Tear resistant	>40 MD / >40 CD per ASTM D882 2 Test Method		
Tensile strength	>40 MD / >40 CD per ASTM D882 2 Test Method		
Adhesive backing	Permanent with clean removability performance. Solvent based		
Operating temperature	15 to 30° C		
Operating humidity	30 to 80% RH		
Lightfastness (Indoor Commercial Window)	Greater than 3 years (with Latex, HP 790 and HP 780 ink supplies). For details: http://www.hp.com/go/supplies/printpermanence .		
Low-solvent Ink			
Waterfastness	Water-resistant		
Dry time	Less than 6 minutes (@ 23°C, 50% RH)		
Shelf time	1 year, unopened in original packaging		
Storage temperature	5 to 40° C		
Storage humidity	5 to 95% RH		
Country of origin	Product of United States		
Ordering information	Product Numbers	Roll sizes	UPC codes
	CG423A	1067 mm x 45.7 m	883585618644
	CG424A	1372 mm x 45.7 m	883585618651
	CG425A	1524 mm x 45.7 m	883585618668
	CG426A	1524 mm x 91.4 m	883585618675
Warranty	HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.		

© 2008 Hewlett-Packard Development Company, L.P.
The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material,
visit<http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-1595 EEE

