


Console Modules

Diagram



(KA9222A)




(KA9272A)



■ PS/2 console support (KA9222A)



■ USB console support (KA9272A)



■ PS/2 local computer support (KA9222A)



■ USB local computer support (KA9272A)

Features

- One console module can control a local computer and a matrix KVM switch
- Local-user operation—access any server on the same switch
- Master-user operation—access all servers on the matrix KVM switch installation
- Control servers regardless of differences in monitor, keyboard, and mouse interfaces
- Auto Signal Compensation (ASC)—no DIP switch setting necessary to compensate for distance
- Superior video quality—support resolutions of up to 1024 x 768 within a distance of up to 150m(KM0216/KM0432), 300m(KM0832); DDC2B
- Lifetime flash firmware upgrades

Specifications

Function			KA9222A	KA9272A
Computer Connections			1	
Console Connections			1	
Connectors	Console Ports	Keyboard	1 x 6-pin Mini-DIN Female (Purple)	1 x USB Type A Female (White)
		Video	1 x HDB-15 Female (Blue)	
		Mouse	1 x 6-pin Mini-DIN Female (Green)	1 x USB Type A Female (White)
	KVM Ports		1 x SPHD-15 Female (Yellow)	1 x SPHD-15 Female (Green)
	Link		1 x RJ-45 Female	
	Power		1 x DC Jack	
Switches	Select		1 x Pushbutton	
LEDs	Link		1 (Green)	
	Local		1 (Orange)	
Environment	Operating Temp.		0–50°C	
	Storage Temp.		–20–60°C	
	Humidity		0–80% RH, Non-condensing	
Physical Properties	Housing		Metal	
	Weight		0.73 kg	0.78 kg
	Dimensions (L x W x H)		20.00 x 7.45 x 4.20 cm	20.00 x 7.45 x 4.20 cm

* The specifications and pictures are subject to change without notice.