

CS1774



- 4-Port USB 2.0 KVME™ Switch
- CS1774 is a multi-computer KVM Switch with built-in 3-in-1 (KVM Switch, USB 2.0 and Ethernet) function. It can simultaneously control 4 servers via a set of USB keyboard, mouse, and monitor. Moreover, the built-in USB and Ethernet Switch ports can rapidly access USB peripheral devices and share Internet resources at ease.




Features

- USB 2.0 KVME™ Switch with Ethernet Hub/USB Hub
- Five auto-sensing dual speed ports (Ethernet/Fast Ethernet) plug-and-play enabled; hub complies with IEEE802.3/IEEE802.3u Standard
- 2 port USB 2.0 Hub built in
- Multiplatform support: compatible with all operation platforms PC(Windows, Linux and most others), Mac and Sun
- With speaker and microphone support
- [Bi-directional switching and flexible interoperability; switch permits independent PC, independent peripheral, and independent audio function, regardless of KVM switch focus](#)
- Buzzer On/Off via hotkey
- Keyboard and mouse emulation for error free booting
- Computer selection via front panel pushbuttons and hotkeys
- superior video quality - up to 2048 x 1536; DDC2B
- OS Compatibility: Windows 98, Windows ME, Windows 2000, Windows 2003, Windows XP, [Windows Vista](#), LINUX, Mac OS 8.6/9/10 and SUN Solaris 8/9.
- SUN/Mac keyboard support and emulation*
 - *1. PC keyboard combinations emulate SUN/Mac keyboards.
 - *2. SUN/Mac keyboards only work with their own computers.

Specification

Computer Connections			4
Port Selection			Hotkeys, Pushbutton
USB Port/ Audio Port Selection			Hotkey
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (White)
		Speaker	1 x Mini Stereo Jack Female (Green)
		Microphone	1 x Mini Stereo Jack Female (Pink)
	KVM Ports	Keyboard	4 x SPHD-15 Female (Green)
		Video	
		Mouse	
		Speaker	4 x Mini Stereo Jack Female (Green)
		Microphone	4 x Mini Stereo Jack Female (Pink)
	Ethernet Hub		5 x RJ-45 Female (Black)
	USB Hub		2 x USB Type A Female (White)
	F/W Upgrade		1 x RJ-11 Female (Black)
	Power		1 x DC Jack(Black)
Switches	Port	4 x Pushbutton	
LEDs	On Line / Selected		4 (Orange)
	USB Link		4 (Green)
	10/100 Mbps		5 (Green)
	LINK(Ethernet)		5 (Green)
Emulation	Keyboard/Mouse		USB
Video			2048 x 1536; DDC2B
Scan Interval			1~99 seconds
Power Consumption			DC 5.3V, 5W
Environment	Operating Temp.		0°~50°C
	Storage Temp.		-20°~60°C
	Humidity		0~80% RH, Non-condensing
Physical Properties	Housing		Metal
	Weight		0.92 kg
	Dimensions (L x W x H)		27.00 x 8.70 x 5.50 cm

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2012 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.